



## STANDARD DOORS

DOOR HEIGHT	'X'	'Y'
UP TO 2250mm	2100mm	2000mm - 3000mm
UP TO 2500mm	1600mm - 2400mm	2000mm - 3000mm
UP TO 2800mm	1600mm - 2700mm	1800mm - 3500mm

## NOTES

IF USING AN ARCHITRAVE AROUND THE DOOR OPENING, USE EITHER OF THE FOLLOWING TWO OPTIONS

1. NARROW ARCHITRAVE (LESS THAN 60mm) AROUND PERIMETER OF THE OPENING
2. WIDE ARCHITRAVE (MORE THAN 60mm) ON THE SIDES FROM THE FLOOR TO THE CEILING AND IN THE CENTRE OF THE LINTEL WITH A NARROW ONE ACROSS THE LINTEL

## **IMPORTANT**

1. PLEASE ENSURE GIB AND ARCHITRAVES ARE ON
2. GARAGE FLOOR IS CLEAR OF ANY OBSTRUCTIONS
3. OTHER TRADESPEOPLE ARE NOT WORKING IN THE GARAGE AT TIME OF INSTALLATION

CHARGES MAY APPLY IF THE ABOVE CRITERIA IS NOT MET



ISSUE	DATE	REVISION	
PROJECT	FIXING DETAILS - SECTIONAL GARAGE DOORS		PROJECT #
CLIENT		DATE # OCT 2024	DWG #
		SCALE @ A3 1:25	
DWG	STANDARD DOORS	DRAWN	GDC-01
		CHKD	REVISION